

TECHNICAL DATA SHEET

TOTAL™

PRODUCT: An alkaline foaming detergent for the exterior of equipment and tanks. Loaded with cleaning agents, this product will clean the toughest soils, leaving a clean shiny surface. Safe for use on aluminum, when used as directed. Apply using foamer and rinse. Follow with PC-303 for showroom shining stainless

BENEFITS:

- Saves clean-up time, provides maximum organic soil removal, and ensures rapid soil penetration.
- Leaves equipment shiny and film free.
- Works well in all water conditions.
- High - foam clings to surfaces foam added contact time.
- Free rinsing that eliminates soap residue.

DIRECTION:

1. Dilute 4-6 oz per Gallon in Foam Sprayer.
2. Spray on to surfaces and allow to stand 5-10 minutes.
3. Using hot water, completely rinse surfaces and allow to air dry.
4. Note: Do Not Mix with Alkaline Solutions with Chlorinated Compounds, keep from freezing, and for industrial use.

SPECIFICATIONS:

CHARACTERISTIC	Liquid	STORAGE STABILITY	Excellent
Ph of 1% SOLUTION	13.2	FREEZING POINT	30°F
FOAM LEVEL	High	WEIGHT PER GALLON	9.20 lbs/Gal
COLOR	Yellow	FIELD TEST PROCEDURE	Sample Size 8.0ml
ODOR	Lemon	PACKAGE SIZES	4x1G, 5G, 15G, 30G, 55G, Tote
RINSIBILITY	Good		

CAUTION:

DOT HAZARDOUS WARNING : UN1760, Corrosive Liquid, N.O.S. (DISODIUM TRIOXOSILICATE PENTAHYDRATE) 8, II

*Please refer to SDS for further precautions.

Last Updated: 12-01-19